

**Amendments to the Claims:**

This listing of claims replaces all prior versions and listings of claims in the application:

**Listing of Claims:**

1. (Currently amended) An apparatus ~~Apparatus~~ for depositing a sheet on a stack, for a delivery unit of a printing machine, said apparatus comprising: at least one stacking device which can be driven so as to rotate about an axis of rotation in order to grasp and deposit the sheet, and includes at least one drag element which is arranged on said at least one stacking device and carried along during rotation, whereby said at least one drag element is provided for shifting deposited sheets for pulling sheets toward a stack abutment, said at least one drag element being arranged, relative to the axis of rotation, on a radial exterior side of the at least one stacking device and movable in the radial direction relative to said at least one stacking device, and the at least one stacking device includes at least two accommodation segments arranged on independently ~~rotating~~ coaxially rotating stacking members which ~~are mounted on a common axis and which can be~~ are actuated together or separately.
2. (Currently amended) The apparatus ~~Apparatus~~ as in Claim 1, wherein said at least one stacking device comprises at least one input means, into which the leading edge of a sheet to be stacked can be fed, and that said at least one drag element is arranged, relative to the axis of rotation, on a radial exterior side of the at least one input means and movable in the radial direction relative to said at least one input means.
3. (Currently amended) The apparatus ~~Apparatus~~ as in Claim 2, wherein respectively said at least one drag element is arranged on each available input means.

4. (Currently amended) The apparatus ~~Apparatus~~ as in claim 3, wherein said at least one drag element is substantially tongue-shaped.
5. (Currently amended) The apparatus ~~Apparatus~~ as in claim 4, wherein said at least one drag element extends so as to project outward from the exterior side.
6. (Currently amended) The apparatus ~~Apparatus~~ as in Claim 5, wherein said at least one drag element extends at an acute angle (wedge angle) outward from the exterior side, against the direction of rotation of the at least one stacking device.
7. (Currently amended) The apparatus ~~Apparatus~~ as in claim 6, wherein said at least one drag element features a rubber material.
8. (Currently amended) The apparatus ~~Apparatus~~ as in claim 7, wherein said at least one drag element features a metal reinforcement.